

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、印刷、流通等权利外，其他权利均归本公司所有。未经许可，不得复制或传播。

FOR-1755 Rev.1.8


2

3

4

5

6




其他接线方式:

ESS-70A-10-X-XX-00


Color: BK:Black 负极
OR:Orange 正极
RD:Red 正极

Contact Termination: B:Busbar
C:Crimp
S:Screw
B/S:Copper Screw




Recommended
Panel Cut-Out

形式一:




Busbar(适配M4螺钉扭矩: 1.2N.m max)

形式二:




Copper Screw (锁合扭矩: 1.5N.m)

形式三:



Crimp

仅Busbar的形式3D展示:



尺寸公差 (mm)					0.05/10 ±1'
0 ~ 30	>30 ~ 60	>60 ~ 100	>100 ~ 150	>150	
±0.20	±0.30	±0.50	±0.70	±1.00	

技术要求/Technical requirements:	
颜色/Color	Black, Orange, Red
锁紧方式/Locking method	卡扣(Buckle)
接线方式/Terminal	Busbar, Screw, Crimp, Copper Screw
外壳材料/Housing material	PA+GF
接触件材料/Connector material	铜合金(Copper alloy)
插入力/Insertion force	65N Max
拔出力/Withdrawal force	>10N
插拔次数/Mechanical working life(mating cycles)	100
安装螺母紧固扭矩/Screw torque	M4/0.4~0.7N.m
接线规格/Wiring specifications	8AWG or 10mm ²
建议剥线长度/Suggested stripping length	8~9mm (Crimp type)
额定电压/Rated voltage	1000V DC
额定电流/Rated current	70A
绝缘电阻/Insulate resistance	≥5000MΩ (drying)
耐电压/Withstanding voltage	4250V/min
接触电阻/Contact resistance	≤0.5mΩ
过电压等级/Overvoltage category	III
污染等级/Pollution degree	3
防护等级/Ingress protection	IP67 (Mated)
使用温度范围/Operating temperature(°C)	-40~+125(including temperature rise)
盐雾/Salt spray	48H
储存温度/Storage temperature(°C)	-40~+85
阻燃等级/Flame retardant ability	UL94-V0
符合RoHS环保要求/Conform to RoHS	Yes
UL4128认证/UL4128 certification	E530802
TUV认证/TUV certification	50581738
满足户外使用/Satisfy outdoor use	Yes

 DEGSON			MATERIAL:		SURFACE/COLOR:			
			MAT NO./REV:		MAT STATUS:			
APPD:	刘剑	2024.01.24	NAME ESS-70A-10-X-XX-00					
CHKD:	于进海	2024.01.21						
DRFT:	张晓瑶	2024.01.17	DRAWING NO.		TYPE	DRAWING STATUS	SCALE	SHEET
	A4		200269749		CUSTOMER DRAWING		1:1	1/1