


| | | REVISIONS | | | |
|-----|-----|------------------------|---------|-------|-------|
| REV | ECO | DESCRIPTION | DATE | BY | APPR |
| A3 | - | RELEASE NEW DWG FORMAT | 08JAN14 | JARRY | |
| A4 | - | ADD COLOR OPTION | 23NOV20 | LOUIE | TOMMY |

REQUIRES CONTACT
RETENTION WEDGE AW2P



NOTES: UNLESS OTHERWISE SPECIFIED


1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER


- 2. MODIFICATIONS: END CAP
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:


IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- MATING PART: AT06-2S* PLUG (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



| CONTACT MIN. INSUL | | MAX. INSUL | TYPICAL | |
|--------------------|-----------|---------------|---------------------------|--|
| SIZE O.D. | | O.D. WIRE RAN | | |
| 40 | 2.24 mm | 3.68 mm | 14 - 20 AWG | |
| 16 | (.088 in) | (.145 in) | (2.0-0.5mm ²) | |








CHART ARE AVAILABLE VIA SPECIAL ORDER.

| PART NUMBER CHART | | | |
|-------------------|-----------------|--|--|
| COLOR | PART NUMBER | | |
| GREY | AT04-2P-EC01 | | |
| BLACK | AT04-2P-EC01BLK | | |
| BLUE | AT04-2P-EC01BLU | | |
| BROWN | AT04-2P-EC01BRN | | |
| GREEN | AT04-2P-EC01GRN | | |
| RED | AT04-2P-EC01RED | | |
| WHITE | AT04-2P-EC01WHT | | |
| YELLOW | AT04-2P-EC01YEL | | |
| ORANGE | AT04-2P-EC01ORG | | |

SEE PART NUMBER CHART PART NUMBER QUANTITY **MATERIALS LIST** UNLESS OTHERWISE SPECIFIED SIGNATURES DATE 1) All dimensions are in metric(mm) 1) All dimensions are in metro(mm).
2) Tolerances are as follows:
1 PL DEC ±0.30
2 PL DEC ±0.15
3 PL DEC ±0.08

Angles ±1° LOUIE 23NOV20 ORION 25NOV20 TOMMY 27NOV20 MATERIAL SPECIFICATIONS CUSTOMER THIS DRAWING IS SUPPLIED FOR THIS DRAWING IS SUPPLIED FOR HINFORMATION ONLY, DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DAT SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHT OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. PROCESS SPECIFICATIONS NEXT ASS'Y

DESCRIPTION ITEM
LS LIST
Amphenol

RECEPTACLE, 2 PIN, AT SERIES, END CAP

DWG NO:

AT04-2P-EC01XXX

REV:

≥

왚

44724 Morley Drive Clinton Township, MI 48036

RECEPTACLE, 2 PIN, AT SERIES, END CAP

B C D DNG NO:
AT04-2P-EC01XXX A4

SCALE: NONE SHEET 1 OF 1

AT Series™ - Contact Size 16 Options

| Machined Contacts, Sockets & Pins | | | | |
|-----------------------------------|---|------------------------------|-------------------|----------|
| Part Number | Description | | AWG | Туре |
| AT60-215-1631 | Male Contact - Pin, Gold-plated 16 14 | | 14 | Machined |
| AT62-209-1631 | Female Contact - Socket, Gold-plated | 16 | 14 | Machined |
| AT60-215-16141 | Male Contact - Pin, Nickel-plated | 16 | 14 | Machined |
| AT62-209-16141 | Female Contact - Socket, Nickel-plated | 16 | 14 | Machined |
| AT60-202-1631 | Male Contact - Pin, Gold-plated | 16 | 16-20 | Machined |
| AT62-201-1631 | Female Contact - Socket, Gold-plated 16 16-20 | | 16-20 | Machined |
| AT60-202-16141 | Male Contact - Pin, Nickel-plated 16 16-20 | | 16-20 | Machined |
| AT62-201-16141 | Female Contact - Socket, Nickel-plated | 16 | 16-20 | Machined |
| AT60-202-1631-22 | Male Contact - Pin, Gold-plated | 16 | 22-24 | Machined |
| AT62-201-1631-22 | Female Contact - Socket, Gold-plated | old-plated 16 22-24 Machined | | |
| AT60-202-16141-22 | Male Contact - Pin, Nickel-plated | 16 | 22-24 | Machined |
| AT62-201-16141-22 | Female Contact - Socket, Nickel-plated | 16 | 16 22-24 Machined | |

| Tooling - Machined Contacts | | | |
|-----------------------------|-------------|--|--|
| Part | Part Number | Description | |
| | CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only) | |
| 3 | CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only) | |

| Contact Removal Tools | | | | |
|-----------------------|---------------|---|--|--|
| Part | Part Number | Description | | |
| 3 | ATRT-100 | Used for removal of contacts for A Series™ products | | |
| | AT11-310-1605 | Contact Removal Tool, Plastic, Size 16 | | |
| | A114017 | Sealing Plug, Size 16, White | | |

| Stamped & Formed Contacts, Sockets & Pins | | | | |
|---|--|------|-------|------------------|
| Part Number | Description | Size | AWG | Туре |
| AT60-14-0144 | Male Contact - Pin, Gold-plated | 16 | 14-16 | Stamped & Formed |
| AT62-14-0144 | Female Contact - Socket, Gold-plated | 16 | 14-16 | Stamped & Formed |
| AT60-14-0122 | Male Contact - Pin, Nickel-plated | 16 | 14-16 | Stamped & Formed |
| AT62-14-0122 | Female Contact - Socket, Nickel-plated | 16 | 14-16 | Stamped & Formed |
| AT60-16-0144 | Male Contact - Pin, Gold-plated | 16 | 16-18 | Stamped & Formed |
| AT62-16-0144 | Female Contact - Socket, Gold-plated | 16 | 16-18 | Stamped & Formed |
| AT60-16-0122 | Male Contact - Pin, Nickel-plated | 16 | 16-18 | Stamped & Formed |
| AT62-16-0122 | Female Contact - Socket, Nickel-plated | 16 | 16-18 | Stamped & Formed |
| AT60-16-0644 | Male Contact - Pin, Gold-plated | 16 | 18-20 | Stamped & Formed |
| AT62-16-0644 | Female Contact - Socket, Gold-plated | 16 | 18-20 | Stamped & Formed |
| AT60-16-0622 | Male Contact - Pin, Nickel-plated | 16 | 18-20 | Stamped & Formed |
| AT62-16-0622 | Female Contact - Socket, Nickel-plated | 16 | 18-20 | Stamped & Formed |
| AT60-16-0844 | Male Contact - Pin, Gold-plated | 16 | 20-22 | Stamped & Formed |
| AT62-16-0844 | Female Contact - Socket, Gold-plated | 16 | 20-22 | Stamped & Formed |
| AT60-16-0822 | Male Contact - Pin, Nickel-plated | 16 | 20-22 | Stamped & Formed |
| AT62-16-0822 | Female Contact - Socket, Nickel-plated | 16 | 20-22 | Stamped & Formed |

| Tooling - Stamped & Formed Contacts | | | |
|-------------------------------------|-------------------------|---|--|
| Part | Part Number Description | | |
| | MFX-3950 | Crimp Die - Size 16, 18-20AWG (S&F contacts only) | |
| | MFX-3953 | Crimp Die - Size 16, 16-18AWG (S&F contacts only) | |
| | MFX-3975 | Crimp Die - Size 16, 14-16AWG (S&F contacts only) | |
| | MFX-3990 | Crimp Die - Size 16, 20-22AWG (S&F contacts only) | |
| | ATT-16-00 | Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only) | |
| | ATT-16-01 | Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only) | |
| | ATT-1612-03 | Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only) | |

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AT04-2P-EC01BLK