


REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A1		RELEASE NEW DRAWING	25Feb17	Jony	TOMMY		



17/16-12 UN THREAD

38.5





NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: THREADED ADAPTER;
- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP04-18-14P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT
SIZE	O.D.	O.D.	WIRE RANGE	RATING
16	2.54 mm (.100in)	3.40 mm (.134 in)	14-20 AWG	

AHDP06-18-14SN-WTA PART NUMBER DESCRIPTION MATERIALS LIST QUANTITY UNLESS OTHERW SIGNATURES DATE **Amphenol** Jony 25Feb17 25Feb17 Orion Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036 25Feb17 Tommy PLUG,18-14 POS,SOCKET CONTACT STANDARD DIA. SEAL, AHDP SERIES THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DASHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION NO RIGH-FOR EMPOLICION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. AHDP06-18-14SN-WTA В CALE: NONE SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AHDP06-18-14SN-WTA