

NOTES: UNLESS OTHERWISE SPECIFIED

1 MATERIAL


HOUSING: THERMOPLASTIC; BLACK SEAL: SILICONE RUBBER


OLAL. OILIOONE ROBBER

- 2. MODIFICATIONS: THREADED ADAPTER;
- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP04-18-20P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND WIRE RANGE:


CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE	CURRENT RATING
20	1.02 mm (.040in)	2.10 mm (.083 in)	16-22 AWG	7.5 AMPS
16	2.54 mm (.100in)	3.40mm (.134 in)	14-20 AWG	13 AMPS





PLUG,18-20 POS,SOCKET CONT.,STANDARD DIA. SEAL, AHDP

AHDP06-18-20SN-WTA



AHDP06-18-20SN-WTA

	7111111111111	0 20014 11171					
	PART NUMBER		DESCRIPTION		ITEM		
QUANTITY		MATERIALS LIST					
1) All dimensions are in metric(mm). 2) Tolerances are a follows: 1 PL DEC ±0.30 f. Angles ±1" 3 PL DEC ±0.01 f. Angles ±1" 3 PL DEC ±0.08 c. Margines ±1" 3 PL DEC ±0.08 c. Margines ±1" CHECKED: Orion 3: ENGINEER:		SIGNATUR	ES DATE	Amphonol			
		DRAWN: Rookie	31JAN18	Amphenol			
		CHECKED: Orion	31JAN18	Sine Systems - www.amphenol-sine.com 44724 Morley Drive			
		ENGINEER:					
		APPROVAL: Tommy	31JAN18	Clinton Township, MI 48036			
		CUSTOMER:		PLUG,18-20 POS,SOCKET CONTACT			
				STANDARD DIA. SEAL, AHDP SERIES			
		RFORMANCE DATA IE PROPERTY OF RATION, NO RIGHTS IMPLIED, ALL OT TO NORMAN	B C- AHDP06-18-20SN-WTA	A1			
NEXT ASS'Y:	MANUFACTURING VARIATION		TIONS.	SCALE: NONE SHEET 1 OF	1		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AHDP06-18-20SN-WTA