





- 1. MATERIAL: HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER
- 2. MODIFICATIONS: N/A
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:
 - IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-3S* RECEPTACLE (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	2.24 mm	3.68 mm	14 - 20 AWG
	(.088 in)	(.145 in)	(2.0-0.5mm²)



PART NUMBER CHART		
COLOR PART NUMBER		
GREY	AT04-3P	
BLACK	AT04-3P-BLK	
BLUE	AT04-3P-BLU	
BROWN	AT04-3P-BRN	
GREEN	AT04-3P-GRN	
RED	AT04-3P-RED	
WHITE	AT04-3P-WHT	
YELLOW	AT04-3P-YEL	
ORANGE	AT04-3P-ORG	



STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

									\vdash
	SEE PART NUMBER CHART		HART	REF: DT043P, DT043P-P004, DT043P-E004				1	
	PART N	IUMBER				DE	SCRIPTION	ITEM]-
QUANTITY		L	MAT	ERI	ALS	LI:	ST		H
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). SIGNATUR			ATURES	DATE		$\overline{}$	mphopol		1
2) Tolerances are a 1 PL DEC ±0.30		DRAWN:	LOUIE	23NOV20			mphenol		
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	24NOV20	Sine Systems - www.amphenol-sine.com		_		
3) Note reference	- 🗴	ENGINEER:			44724 Morley Drive Clinton Township, MI 48036				
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	25NOV20	20			┨	
		CUSTOMER:			RECEPTACLE, 3 PIN, AT SERIES				
		THIS DRAWING	IS SUPPLIED FO		, ,				
PROCESS SPECIFICATIONS: SPECIFICATIONS AND PERFORMANCE DATA SIZE TYPE SHOWN HEREON ARE THE PROPERTY OF THE AMPHENCL CORPORATION NO RIGHTS OF REPRODUCTION ARE MIRED ALL. ATTOMATICAL SIZE TO THE AMPHENCE OF		AT04-3P-XXX	A4						
NEXT ASS'Y:		MANUFACTURII				1	1		

AT04-3P-XXX

DWG NO:

RECEPTACLE, 3 PIN, AT SERIES

¥

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined	
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined	
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined	
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined	
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined	
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined	
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined	
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined	
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined	
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined	
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined	
AT62-201-16141-22	Female Contact - Socket, Nickel-plated 16 22-			Machined	

Tooling - Machined Contacts			
Part	Part Number	Description	
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)	
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)	

Contact Removal Tools				
Part	Part Number	Description		
3	ATRT-100	Used for removal of contacts for A Series™ products		
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16		
	A114017	Sealing Plug, Size 16, White		

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed

Tooling - Stamped & Formed Contacts			
Part	Part Number Description		
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)	
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)	
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)	
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)	
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)	
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)	
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)	

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: AT04-3P-BLK