

			REVISIONS			
REV ECO			DESCRIPTION	DATE	BY	APPR
	A3	-	RELEASE NEW DWG FORMAT	02JAN14	JARRY	
	A4	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY

RECEP., 2 PIN,AT SERIES,REDUCED DIA. WIRE SEAL,END CAP


DWG NO:

AT04-2P-EC01XXX

REV:

≴

ITEM



NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER


2. MODIFICATIONS: END CAP;

REDUCED DIA. WIRE SEAL


- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:


IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-2S* PLUG (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	
SIZE	O.D.	O.D.	WIRE RANGE	
16	1.35 mm	3.05 mm	14 - 20 AWG	
10	(.053 in)	(.120 in)	(2.0-0.5mm ²)	





PART N	PART NUMBER CHART				
COLOR	PART NUMBER				
GREY	AT04-2P-MM01				
BLACK	AT04-2P-MM01BLK				
BLUE	AT04-2P-MM01BLU				
BROWN	AT04-2P-MM01BRN				
GREEN	AT04-2P-MM01GRN				
RED	AT04-2P-MM01RED				
WHITE	AT04-2P-MM01WHT				
YELLOW	AT04-2P-MM01YEL				
ORANGE	AT04-2P-MM01ORG				




CHART ARE AVAILABLE VIA SPECIAL ORDER.

	SEE PART NUME		HART	REF: DT04-2P-CE01, DT04-2P-CE03				
	PART N	NUMBER			DE	SCRIPTION		ITEM
QUANTITY		-	MAT	ERI	ALS LI	ST		
	WISE SPECIFIED	SIGN	ATURES	DATE	^	mnho	nal	
1) All dimensions a 2) Tolerances are a 1 PL DEC ±0.30		DRAWN:	LOUIE	23NOV20	Amphenol			
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	25NOV20	Sin	e Systems - www.ampher	nol-sine.com	_
3) Note reference = X		ENGINEER:			44724 Morley Drive			
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	27NOV20		Clinton Township, MI 480	J36	
		CUSTOMER:			REC	EPTACLE, 2 PIN, A	T SERIES,	
			G IS SUPPLIED F		REDUCED	DIAMETER WIRE	SEAL, END	CAP
PROCESS SPECIFICATIONS: NEXT ASSY:		SPECIFICATION SHOWN HEREIN THE AMPHENO OF REPRODUC	ONLY. DESIGN INS AND PERFORM ON ARE THE PR OL CORPORATIO CTION ARE IMPL ARE SUBJECT TO	RMANCE DATA ROPERTY OF ON. NO RIGHTS LIED. ALL	B C-	AT04-2P-MM	101XXX	A4
		DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		SCALE: NONE		SHEET 1 OF	1	

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins						
Part Number	Description		AWG	Туре		
AT60-215-1631 Male Contact - Pin, Gold-plated		16	14	Machined		
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined		
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined		
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined		
AT60-202-1631	Male Contact - Pin, Gold-plated		16-20	Machined		
AT62-201-1631	Female Contact - Socket, Gold-plated		16-20	Machined		
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined		
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined		
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined		
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined		
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined		
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined		

Tooling - Machined Contacts				
Part	Part Part Number Description			
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)		
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)		

Contact Removal Tools						
Part Part Number		Description				
3	ATRT-100	Used for removal of contacts for A Series™ products				
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16				
	A114017	Sealing Plug, Size 16, White				

Stamped & Formed Contacts, Sockets & Pins						
Part Number Description			AWG	Туре		
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed		
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed		
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed		
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed		
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed		
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed		
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed		
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed		
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed		
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed		
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed		
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed		
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed		
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed		
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed		
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed		

Tooling - Stamped & Formed Contacts					
Part	Part Number	Description			
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)			
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)			
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)			
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)			
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)			
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)			
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)			

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AT04-2P-MM01BLK