

38.3 40.3 └─1 11/16-12 UN THREAD



1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK

SEAL: SILICONE RUBBER

2. MODIFICATIONS: THREADED ADAPTER;

THIN WALL DIA. WIRE SEAL


3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C. 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP04-24-31S* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND WIRE RANGE:


CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT
SIZE	O.D.	O.D.	WIRE RANGE	RATING
16	2.23 mm (.088in)	2.69 mm (.106 in)	14-20 AWG	13 AMPS

REVISIONS						
REV	ECO	DESCRIPTION	DATE	BY	APPR	
A1		RELEASE NEW DRAWING	13NOV15	SULLEN	TOMMY	
A2	C0765S	UPDATE SPECIFICATIONS	23NOV17	ROOKIE	TOMMY	
A3	C0870S	Change the appearance of the retaining ring	26JUN18	KASOON	TOMMY	
A4	C1001S	CHANGE THE WIRE SIZE	28DEC18	BROOK	TOMMY	



TITLE: RECEP,24-31 POS, PIN CONT., THIN WALL WIRE DIA. SEAL, AHDP

DWG NO: AHDP06-24-31PT-WTA REV: A4 SH: 1



	AHDP06-24-31PT-WTA							
	PART NUMBER			DESCRIPTION				ITEM
QUANTITY		1	MAT	ERI	ALS LI	ST		
1) All dimensions are in metric/mm). 2) Tolerances are as follows. 1 PL DEC 30.30 Fractions ±1/64 2) PL DEC 30.16 Angles ±1* 3) Note reference =		SIGNATURES DATE		Amphonol				
		DRAWN:	BROOK	28DEC18	Amphenol			
		CHECKED:	ORION	28DEC18	Sine Systems - www.amphenol-sine.com			_
		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036			
		APPROVAL:	TOMMY	28DEC18				
		FLOG,24-31 FOS, FIN CONTACT						
				THIN WALL WIRE DIA. SEAL, AHDP SERIES				
PROCESS SPECIFICATIONS:		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL		B C-	AHDP06-24-3		A4	
NEXT ASS'Y:				SCALE: NONE		SHEET 1 OF	1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AHDP06-24-31PT-WTA