


2. MODIFICATIONS: THREADED ADAPTER; REDUCED DIA. WIRE SEAL


- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25℃.
 - 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP04-24-19S* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.


6 CONTACT SIZE AND WIRE RANGE:

CONTAC SIZE	T MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE	CURRENT RATING
12	2.46 mm (.097 in)	4.01 mm (.158 in)	10-14 AWG	25 AMPS
16	1.35 mm (.053in)	3.05 mm (.120 in)	14-20 AWG	13 AMPS



REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A1		RELEASE NEW DRAWING	13NOV15	SULLEN	TOMMY		
A2	C0765S	UPDATE SPECIFICATIONS	23NOV17	ROOKIE	TOMMY		
A3	C0870S	Change the appearance of the retaining ring	26JUN18	KASOON	TOMMY		





	AHDP06-24-19PR-WTA									
	PART NUMBER			DESCRIPTION			ITEM] -		
QUANTITY	MATERIALS LIST						┢			
UNLESS OTHERWISE SPECIFICATION) All dimensions are in metric(ripm). 2) Tolerances are as follows: 1PL DEC 20.5 Fractions ±1.04 Angles ±1* 3) Note reference =		SIGN	ATURES	Amphone		nol		1		
		DRAWN:	KASOON	26JUN18	Amphenol					
		CHECKED:	ORION	26JUN18	Sine Systems - www.amphenol-sine.com			_		
		ENGINEER:		44724 Morley Drive Clinton Township, MI 48036						
		APPROVAL:	TOMMY	26JUN18	Clinton Township, MI 48036					ł
		CUSTOMER:			PLUG,24-19 POS,PIN CONTACT					
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL INMENSIONS ARE SI NIFICT TO NORMAI		REDUCED DIA. SEAL, AHDP SERIES						
PROCESS SPECIFICATIONS:				В	C-	AHDP06-24-19		A3		
NEXT ASS'Y:	TASSY: MANUFACTURING VARIATIO		ING VARIATIONS	S.	SCALE: N	ONE		SHEET 1 OF	1]

DWG NO: AHDP06-24-19PR-WTA REV: A3 SH: 1

PLUG,24-19 POS, PIN CONT., REDUCED DIA. SEAL, AHDP

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AHDP06-24-19PR-WTA