

38.3 10.7 40.3 11/16-12 UN THREAD



1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK

SEAL: SILICONE RUBBER

2. MODIFICATIONS: THREADED ADAPTER;


THIN WALL DIA. WIRE SEAL

3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP04-24-31P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6 CONTACT SIZE AND WIRE RANGE:

| CONTACT | MIN. INSUL | MAX. INSUL | TYPICAL | CURRENT |
|---------|---------------------|----------------------|------------|---------|
| SIZE | O.D. | O.D. | WIRE RANGE | RATING |
| 16 | 2.23 mm (.088in) | 2.69 mm (.106 in) | 14-20 AWG | 13 AMPS |

| | | REVISIONS | | | |
|-----|--------|---|---------|--------|-------|
| REV | ECO | DESCRIPTION | DATE | BY | APPR |
| A1 | | RELEASE NEW DRAWING | 13NOV15 | SULLEN | TOMMY |
| A2 | C0765S | UPDATE SPECIFICATIONS | 23NOV17 | ROOKIE | TOMMY |
| A3 | C0870S | Change the appearance of the retaining ring | 26JUN18 | KASOON | TOMMY |
| A4 | C1001S | CHANGE THE WIRE SIZE | 28DEC18 | BROOK | TOMMY |



| | AHDP06-24-31ST-WTA PART NUMBER | | | | | | | | |
|---|--------------------------------|---|------|-------------|----------------------------|---------------|-----------|----------|------|
| | | | | DESCRIPTION | | | ITEM | | |
| QUANTITY | | MA | XTE | ERI | ALS L | IST | | | |
| UNLESS OTHERWISE SPECIFIED | | SIGNATURES DATE | | Amphenol | | | | | |
| 1) All dimensions are in metric(mm). 2) Tolerances are as foliows: 1 PL DEC 35.01 2 PL DEC 35.01 3 PL DEC 35.06 3 PL DEC 45.08 3) Note reference = MATERIAL SPECIFICATIONS: | | DRAWN: BROO | OK . | 28DEC18 | <i></i> | ипр | | | |
| | | CHECKED: ORIC | W | 28DEC18 | 44724 Morley Drive | | | | |
| | | ENGINEER: | | | | | | | |
| | | APPROVAL: TOM | W | 28DEC18 | Clinton Township, MI 48036 | | | | |
| | | CUSTOMER: | | | PLUG | ,24-31 POS, S | SOCKET | CONTAC | Γ |
| | | THIS DRAWING IS SUF | | | THIN WA | LL WIRE DIA | . SEAL, A | AHDP SEF | RIES |
| PROCESS SPECIFICATIONS: | | SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAI | | B C- | AHDP06 | -24-315 | ST-WTA | REVISION | |
| NEXT ASS'Y: | | | | SCALE: NONE | | SH | EET 1 OF | 1 | |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AHDP06-24-31ST-WTA