



REVISIONS										
REV	ECO	DESCRIPTION	DATE	BY	APPR					
A1	-	RELEASE NEW DRAWING	10APR18	ROOKIE	TOMMY					
A2	-	REVISED DESCRIPTION	12JUN19	JAH	DH					


TITLE: HYPERBUSS AT 4WAY RECP,4 PIN BUSBAR NI-PLATED, BLACK


REV: A2 SH:





21





NOTES: II	INII ECC	OTHERWISE	<b>CDECIEIED</b>

- 1. MATERIAL: HOUSING: THERMOPLASTIC, BLACK SEAL:SILICONE RUBBER CONTACT: COPPER ALLOY
- 2. MODIFICATIONS: BLACK, 4 PIN BUSBAR WITH NICKEL PLATED
- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 26 AMPS MAXIMUM FOR THE 4 PIN BUSBAR
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C.
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION).
  - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
  - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-4S\* PLUG (\* = AVAILABLE MODIFICATIONS)

5 ORIENTATION OF "Amphenol" AND "-EP13" TO BE OPTIONAL

6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

	AT04-4P-EP13		REF: DT044P-EP13				
	PART N	PART NUMBER		DESCRIPTION		ITEM -	
QUANTITY	MATERIALS LIST						
2) I clerances are as titlorus: 1764 19 FL DEC 30 Fractions 1764 3 PL DEC 40.08 3) Note reference =   MATERIAL SPECIFICATIONS:  PROCESS SPECIFICATIONS.		SIGNATUR	ES DATE	Ampnenoi		nol.	
		DRAWN: ROOKIE	09APR18				
		CHECKED: ORION	09APR18			_	
		ENGINEER:					
		APPROVAL: TOMMY	09APR18	HYPERBUSS AT 4WAY RECEPTACLE			
		CUSTOMER:					.
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION, NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL		SIZE TYPE	USBAR NICKEL-PL	RE	EVISION
				B C-	AT04-4P-I	SHEET 1 OF	1

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:
AT04-4P-EP13