
| REVISIONS | | | | | |
|-----------|-----|---------------------|-----------|-------|-------|
| REV | ECO | DESCRIPTION | DATE | BY | APPR |
| 01 | - | PRELIMINARY DRAWING | 24/SEP/19 | PETER | TOMMY |





REQUIRES CONTACT

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:

 - 3.1 CURRENT RATING: 25 AMPS
 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2
 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 3.5 MOISTURE RESISTANCE: PHOF (MATCH CONDITION)

 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP04-6P* RECEPTACLE. (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.





STANDARD SEAL


| CONTACT SIZE | MIN. INSUL O.D. | | TYPICAL WIRE RANGE |
|-----------------|----------------------|----------------------|-----------------------------|
| 12 | 3.40 mm (.134 in) | 4.95 mm (.195 in) | 10 - 14 AWG (6.0-2.0mm²) |

REDUCED DIAMETER SEAL


| CONTACT | MIN. INSUL | | TYPICAL |
|---------|------------|-----------|---------------------------|
| SIZE | O.D. | O.D. | WIRE RANGE |
| 12 | 2.46 mm | 4.01 mm | 12 - 14 AWG |
| 12 | (.097 in) | (.158 in) | (3.0-2.0mm ²) |








| PART NUMBER CHART | | | |
|-------------------|-----------------|------------------|--|
| COLOR | P/N W/ STD SEAL | P/N W/ RD SEAL | |
| GREY | ATP06-6S-OMGRY | ATP06-6S-OMRDGRY | |
| BLACK | ATP06-6S-OMBLK | ATP06-6S-OMRDBLK | |
| BLUE | ATP06-6S-OMBLU | ATP06-6S-OMRDBLU | |
| BROWN | ATP06-6S-OMBRN | ATP06-6S-OMRDBRN | |
| GREEN | ATP06-6S-OMGRN | ATP06-6S-OMRDGRN | |
| RED | ATP06-6S-OMRED | ATP06-6S-OMRDRED | |
| WHITE | ATP06-6S-OMWHT | ATP06-6S-OMRDWHT | |
| YELLOW | ATP06-6S-OMYEL | ATP06-6S-OMRDYEL | |





REFER TO PART NUMBER CHART FOR **AVAILABLE CONNECTOR COLORS**

| SEE PART N | JMBER CHART | | | | | ٦ |
|---|---|-----------|--|-------------|---------|-----|
| PART NUMBER | | | DESCRIPT | ION | ITE | И - |
| QUANTITY | MA | TERI | ALS LIST | | • | 7 |
| UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions +1/64 | SIGNATURE: | | Amphenol | | | |
| 1 PL DEC ±0.30 Fractions ±1/64 2 PL DEC ±0.15 Angles ±1° 3 PL DEC ±0.08 X | CHECKED: ORION.LI ENGINEER: | 24/SEP/19 | Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036 | | | |
| MATERIAL SPECIFICATIONS: | CUSTOMER: TOMMY.XIE | 24/SEP/19 | STRUCTURE+, OVERMOLD-COMPATIBLE | | | 1 |
| PROCESS SPECIFICATIONS: | SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL | | SIZE TYPE DWG NO: | P06-6S-OMXX | REVISIO | N |
| NEXT ASS'Y: | | | SCALE: NONE | SHEET | 1 of 1 | |

TITLE: STRUCTURE+, OVERMOLD-COMPATIBLE, PLUG, 6 SOCKET, ATP SERIES DWG NO: ATP06-6S-OMXXX

REV: 01 SH:

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

ATP06-6S-OMBLK