



NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL: COPPER ALLOY

2. PLATING: SEE PART NUMBER CHART

3. CONTACT SIZE: 16

4. SPECIFICATIONS:

4.1 CURRENT RATING: 13 AMPS

4.2 CONTACT MILLIVOLT DROP: 60 MILLIVOLT DROP @ 13 AMP TEST CURRENT.

4.3 RoHS COMPLIANT

5. RECOMMENDED WIRE RANGE: 16 - 20 AWG

6. AVAILABLE HAND CRIMPER: CA-5D12

7. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY

PART NUMBER CHART				
PLATING	PART NUMBER			
GOLD	AT60-202-1631			
NICKEL	AT60-202-16141			

	SEE PART NUMBER CHART									
	PART NUMBER		DESCRIPTION					ITEM		
QUANTITY MATERIALS LIST										
UNLESS OTHER	WISE SPECIFIED	SIGNATURE	S DAT	Ξ.	Amphenol					
2) Tolerances are a		D.PARKS	10/OCT/	T/13 Ampher						
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:		_	Sine Systems - www.amphenol-sine.com					
3) Note reference =		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036					
		APPROVAL:	Cilition Township, Wi 46036			030				
		CUSTOMER:			CONTACT, PIN, SOLID, SIZE 16, 16-20 AWG, AT & AHD-9 SERIES					
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL								
				TS A	C-	AT60-202-1	I6XXX	A6		
				SCALE:	ONE		SHEET 1	of 1		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AT60-202-1631