


ATP06-48

NOTES:

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 25 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP04-4P* RECEPTACLE. (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



| PART NUMBER CHART | | | | | | | |
|-------------------|-----------------|--|--|--|--|--|--|
| COLOR | PART NUMBER | | | | | | |
| GREY | ATP06-4S-RD01 | | | | | | |
| BLACK | ATP06-4S-RD01BK | | | | | | |

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.

34.9

REDUCED DIAMETER WIRE SEAL

055 DADTAH BADED OLIA DT

REV

АЗ

ECO

| | SEE PART NUMBER CHART | | | | | | | | |
|---|-----------------------|---|-----------|----------------------------|--|-----------|---------|-------------|------|
| | PART N | IUMBER | | | DESCRIPTION | | | | ITEM |
| QUANTITY | | r | TAN | ERI | ٩LS | S LI | ST | | |
| UNLESS OTHERWISE SPECIFIED | | SIGNATURES | | 6 DATE | Amphana | | | | |
| 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 Fractions ±1/64 Angles ±1° | DRAWN: | D.PARKS | 18/OCT/13 | Amphenol | | | |) [| |
| | | CHECKED: | | | Sine Systems - www.amphenol-sine.com | | | | |
| 3) Note reference =X | | ENGINEER: | | | 44724 Morley Drive Clinton Township, MI 48036 | | | | |
| | | APPROVAL: | | | Clinton Township, Ivii 40000 | | | | |
| | | CUSTOMER: | | | PLUG, 4 SOCKET, ATP SERIES, | | | | |
| | | SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL | | REDUCED DIAMETER WIRE SEAL | | | | ٩L | |
| | | | | B | C- | ATP06-4S- | RD01XX | A3 | |
| NEXT ASS'Y: | | DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. | | SCALE: | IONE | | SHEET 1 | of 1 | |

REVISIONS

DATE

18/OCT/13

APPR

BY

DRP

DESCRIPTION

RELEASE NEW DWG FORMAT

ATP06-4S-RD01XX

PLUG, 4 SOCKET, ATP SERIES, REDUCED DIA WIRE SEAL

A3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

ATP06-4S-RD01BK