


REVISIONS								
REV	ECO	DESCRIPTION	DATE	BY	APPR			
A1	-	RELEASE NEW DRAWING	17/OCT/18	BROOK	TOMMY			
A2	-	ADD MORE MATERIAL NOTES	24/OCT/18	ROOKIE	TOMMY			



AHDM04-18-20SR

⋧

ITEM

NOTES: UNLESS OTHERWISE SPECIFIED


1. MATERIAL:

SHELL: ZINC ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: THREADED HOUSING; REDUCED DIA. SEAL
- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
 - 3.5 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDM06-18-20P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.


6. CONTACT SIZE AND WIRE RANGE:

CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE	CURRENT RATING	
20	1.02 mm (.040 in)	2.41 mm (.095 in)	16-22 AWG	7.5 AMPS	
16	1.35 mm (.053 in)	3.05 mm (.120 in)	14-20 AWG	13 AMPS	



RECOMMENDED PANEL MOUNTING HOLE

RECOMMENDED PANEL THICKNESS:1.6 TO 4.7MM



	AHDM04-18-20SR		R						T
	PART NUMBER			DESCRIPTION					T
QUANTITY	TY MA			TERIALS LIST					
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm).		SIGNATURES DATE		Amphenol					
2) Tolerances are a		DRAWN:	ROOKIE	24/OCT/18		ипрпе		"	
2 PL DEC ±0.15 3 PL DEC ±0.06	Angles ±1°	CHECKED:	ORION	24/OCT/18	Sin	enol-sine.com			
3) Note reference	- 🗴	ENGINEER:			44724 Morley Drive				
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	24/OCT/18		Clinton Township, MI 4	8036		_
PROCESS SPECIFICATIONS: NEXT ASS Y:		CUSTOMER:			RECPT	, 18 SZ 20 SOC,	RD. WIDE	ТН	ID
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL			,	,			
				B C-	AHDM04-1	8-20SR		/	
				SCALE: NONE		SHEET 1	OF		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AHDM04-18-20SR