

NOTES: UNLESS OTHERWISE SPECIFIED


1. MATERIAL:


HOUSING: THERMOPLASTIC CONTACT: COPPER ALLOY PLATING: NICKEL UNDERPLATE

SEE CHART FOR OVERALL FINISH


2. MODIFICATIONS: RIGHT ANGLE PCB MOUNT, SCREW BOSS, KEYED, HOUSING COLOR

- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-6S* PLUG (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.







| REVISIONS | | | | | | | |
|-----------|-----|----------------------|-----------|-------|-------|--|--|
| REV | ECO | DESCRIPTION | DATE | BY | APPR | | |
| A1 | - | RELEASE | 7JUN2018 | JAH | | | |
| A2 | - | UPDATE DRAWING | 19/MAR/19 | BROOK | TOMMY | | |
| A3 | - | MODIFIED DESCRIPTION | 12JUL19 | BROOK | TOMMY | | |



RECOMMENDED PCB LAYOUT







RIGHT ANGLE RECEPT, AT 6 PIN, SCREW BOSS, BOARDLOCK

ATF13-6PX-BM1X

SH

| PART NUMBER | CONTACT PLATING | HSG COLOR | PAI | |
|---------------|--------------------|--------------|-------|--|
| ATF13-6P-BM11 | GOLD | BLACK | ATF13 | |
| ATF13-6P-BM13 | TIN | BLACK | ATF13 | |
| | • | • | | |

| PART NUMBER | CONTACT PLATING | HSG COLOR | | |
|-------------------|--------------------|--------------|--|--|
| ATF13-6P2-BM11BLU | GOLD | BLUE | | |
| ATF13-6P2-BM13BLU | TIN | BLUE | | |

| | | | | ł |
|-----------------------|---|------|------|---|
| SEE PART NUMBER CHART | REF: DTF136P, DTF136P-G003, DTF136P2-G003 | | S.F. | |
| PART NUMBER | DESCRIPTION | ITEM | | |
| | | | | |

| | PART N | NUMBER | | | DESCRIPTION | | | | | ITEM | | |
|--|-----------|--|------------|----------------------------|-----------------------------------|-------|--------|----------|---------------|------|---|--|
| QUANTITY | | MATERIALS LIST | | | | | | | | | | |
| UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). | | SIGNATURES DATE | | | ^ | \ m r | s b | <u> </u> | $\overline{}$ | | | |
| 2) Tolerances are a 1 PL DEC ±0.30 | | DRAWN: | BROOK.DING | 12/JUL/19 | Amphe | | | | | HOI | | |
| 2 PL DEC ±0.15 3 PL DEC ±0.08 Angles ±1* 3) Note reference = X | | CHECKED: | ORION.LI | 12/JUL/19 | 44724 Morley Drive | | | | | m | | |
| | | ENGINEER: | | | | | | | | | | |
| MATERIAL SPECIFICA | APPROVAL: | TOMMY.XIE | 12/JUL/19 | Clinton Township, MI 48036 | | | | | | | | |
| PROCESS SPECIFICATIONS: NEXT ASS'Y: | | CUSTOMER: THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES. | | | RIGHT ANGLE RECEPTACLE, AT 6 PIN, | | | | | | | |
| | | | | | SCREW BOSS, BOARDLOCK | | | | | | | |
| | | SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMPNSIONS ARE SUBJECT TO NORMAL | | В | C- | ATF13 | -6PX-B | | | A3 | | |
| | | MANUFACTURING VARIATIONS. | | | SCALE: N | ONE | | | SHEET 1 | OF | 1 | |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

ATF13-6P2-BM11BLU