



RECEPTACLE, 4 PIN, ATM SERIES

ATM04-4P-XXX





NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: N/A

3. SPECIFICATIONS:

3.1 CURRENT RATING: 7.5 AMPS

3.2 OPERATING TEMPERATURE: -55°C TO +125°C

3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.

3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)

3.6 MATING CYCLE DURABILITY: 100 CYCLES


3.7 RoHS COMPLIANT

4. MATING PART: ATM06-4S* PLUG
(* = MODIFICATIONS AND COLORS)


5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
20	1.35 mm (.053 in)	3.05 mm (.120 in)	16 - 22 AWG



PART NUMBER CHART		
COLOR	PART NUMBER	
GREY	ATM04-4P	
BLACK	ATM04-4P-BLK	
BLUE	ATM04-4P-BLU	
BROWN	ATM04-4P-BRN	
GREEN	ATM04-4P-GRN	
RED	ATM04-4P-RED	
WHITE	ATM04-4P-WHT	
YELLOW	ATM04-4P-YEL	



SEE PART NUMBER CHART DESCRIPTION ITEM PART NUMBER QUANTITY MATERIALS LIST UNLESS OTHERWISE SPECIFIED **Amphenol** SIGNATURES DATE 1) All dimensions are in metric(mm) D.PARKS 18/JUN/13 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 Fractions ±1/64 Angles ±1° Sine Systems - www.amphenol-sine.com 44724 Morley Drive 3) Note reference = X Clinton Township, MI 48036 MATERIAL SPECIFICATIONS: RECEPTACLE, 4 PIN, ATM SERIES THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SIZE PROCESS SPECIFICATIONS SHOWN HEREON ARE THE PROPERTY OF **A3** В ATM04-4P-XXX THE AMPHENOL CORPORATION. NO RIGHT OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. NEXT ASS'Y: SCALE: NONE SHEET 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 $\frac{\text{Amphenol}}{\text{ATM04-4P}}$