


1		
21.0	AMPHEN ATO4-4	1
<u> </u>		

	REVISIONS						
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A3	-	RELEASE NEW DWG FORMAT	11DEC13	DRP	-		
A4	C0540S	UPDATE DIMENSIONS	22JUL16	JONY	TOMMY		
A5	-	ADD COLOR OPTION	23NOV20	LOUIE	TOMMY		







STRAIN RELIEF END CAP -BLACK - ALL CONNECTORS

REFER TO PART NUMBER CHART FOR AVAILABLE CONNECTOR COLORS

SEE PART NUMBER CHART

NOTES: UNLESS OTHERWISE SPECIFIED


1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER


- 2. MODIFICATIONS: STRAIN RELIEF END CAP
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE:

IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)

- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-4S* PLUG (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL		TYPICAL
SIZE	O.D.		WIRE RANGE
16	2.24 mm	3.68 mm	14 - 20 AWG
	(.088 in)	(.145 in)	(2.0-0.5mm²)



PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	AT04-4P-SR01GRY			
BLACK	AT04-4P-SR01BLK			
BLUE	AT04-4P-SR01BLU			
BROWN	AT04-4P-SR01BRN			
GREEN	AT04-4P-SR01GRN			
RED	AT04-4P-SR01RED			
WHITE	AT04-4P-SR01WHT			
YELLOW	AT04-4P-SR01YEL			
ORANGE	AT04-4P-SR01ORG			

	OLL:/III	OIVIDELLO							
	PART N	NUMBER		DESCRIPTION			ITEM		
QUANTITY		r	MATERIALS LIST						
UNLESS OTHER		SIGN	ATURES	DATE	^	ma m h a			
All dimensions a Tolerances are a PL DEC ±0.30		DRAWN:	LOUIE	23NOV20		mphe		l	
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION	25NOV20	Sin	e Systems - www.amphe	nol-sine.com		_
3) Note reference	- ∕x	ENGINEER:			44724 Morley Drive Clinton Township, MI 48036				
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	27NOV20					
MATERIAL SPECIFICA	HONS.	CUSTOMER:			REC	EPTACLE, 4 PIN, A	AT SERIES	3,	
			3 IS SUPPLIED			STRAIN RELIEF EN	ND CAP		
PROCESS SPECIFICATIONS: NFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE AS SPECIFICATIONS AND PERFORMANCE AS SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHT OF REPRODUCTION ARE MIPLED. ALL DIMENSIONS ARE SUBJECT TO NORMAL DIMENSIONS ARE SUBJECT TO NORMAL		ORMANCE DATA ROPERTY OF ION. NO RIGHTS PLIED. ALL TO NORMAI	B C-	AT04-4P-SF	R01XXX		15		
NEXT ASS'Y: DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		SCALE: NONE		SHEET 1	OF	1			

DWG NO: AT04-4P-SR01XXX

RECEPTACLE, 4 PIN, AT SERIES, STRAIN RELIEF END CAP

REV: A5

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined

Tooling - Machined Contacts			
Part	Part Number	Description	
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)	
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)	

Contact Removal Tools			
Part	Part Number	Description	
3	ATRT-100	Used for removal of contacts for A Series™ products	
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16	
	A114017	Sealing Plug, Size 16, White	

Stamped & Formed Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed

Tooling - Stamped & Formed Contacts			
Part	Part Number	Description	
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)	
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)	
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)	
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)	
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)	
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)	
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)	

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

AT04-4P-SR01BLK