

NOTES: UNLESS OTHERWISE SPECIFIED

ATP4P-BT-YW

YELLOW

- 1. THIS PART IS USED ON ATP04-4P RECEPTACLE ANY MODIFICTION DOES NOT INCLUDE AN END CAP.
- 2. TEMPERATURE RATING : -29°C TO +100°C [-20°F TO +212°F]
- 3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

	SEE PART N	CHART	REF: DTP4P-BT , DTP4P-BT-BK , DTP4P-BT-YW							
	PART NUMBER			DESCRIPTION						ITEM
QUANTITY			MAI	ERI	ALS) LI	ST			
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 3) Note reference = MATERIAL SPECIFICATIONS:		SIGNATURES DRAWN: BROOKDING		DATE		Amphenol				
				13MAR20		1				
		CHECKED: ORION.LI		16MAR20	Sine Systems - www.amphenol-sine.com					
		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036					
		APPROVAL:	TOMMY.XIE	18MAR20	Official Township, Wil 40030					
PVC PROCESS SPECIFICATIONS: NEXT ASS'Y:		CUSTOMER:	BOOT, ATP ,4 WAY, RECEPTACLE							
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL			SIZE	TYPE	DWG NO:			REVISION
					Α	C-	ATP4P-BT-XX			
					SCALE: N	ONE			sнеет 1	of 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

ATP4P-BT-YW