

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

5600230445

Status:

Active

Overview:

Mini50 Connection Systems

Description:

CTX50 Receptacle Terminal, Unsealed, Tin Plating, S-Grip, B-Wind, Right Payoff

- Documents:
- Drawing (PDF)

Product Specification PS-560023-001-001 (PDF)

Application Specification AS-560023-001-001 (PDF)

Application Specification AS-560023-001-CH-001 (PDF)

Application Specification AS-560023-001-FR-001 (PDF)


Packaging Specification 313025040-000 (PDF)

Test Summary TS-560023-001-001 (PDF)

RoHS Certificate of Compliance (PDF)

Product Literature (PDF)

|                                |                                                                                                                                                           |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| General                        |                                                                                                                                                           |
| Product Family                 | Crimp Terminals                                                                                                                                           |
| Series                         | 560023                                                                                                                                                    |
| Application                    | Power, Wire-to-Board                                                                                                                                      |
| Comments                       | Right Reel Payoff <br><br>For automatic and semi-automatic crimping, use Left Reel Payoff terminals. See Sales Drawing for Left Reel Payoff Part Numbers. |
| Crimp Quality Equipment        | Yes                                                                                                                                                       |
| Overview                       | Mini50 Connection Systems                                                                                                                                 |
| Product Name                   | CTX50                                                                                                                                                     |
| UPC                            | 889056777667                                                                                                                                              |
| Physical                       |                                                                                                                                                           |
| Durability (mating cycles max) | 10                                                                                                                                                        |
| Gender                         | Female                                                                                                                                                    |
| Grip Code                      | S                                                                                                                                                         |
| Material - Metal               | Copper Alloy                                                                                                                                              |
| Material - Plating Mating      | Tin                                                                                                                                                       |
| Net Weight                     | 0.049/g                                                                                                                                                   |
| Packaging Type                 | Reel                                                                                                                                                      |
| Termination Interface: Style   | Crimp or Compression                                                                                                                                      |
| Wire Insulation Diameter       | 0.75-1.05mm                                                                                                                                               |
| Wire Size AWG                  | N/A                                                                                                                                                       |
| Wire Size mm²                  | 0.13                                                                                                                                                      |
| Electrical                     |                                                                                                                                                           |
| Current - Maximum per Contact  | 4.0A                                                                                                                                                      |
| Voltage - Maximum              | 14V DC                                                                                                                                                    |
| Material Info                  |                                                                                                                                                           |
| Reference - Drawing Numbers    |                                                                                                                                                           |
| Application Specification      | AS-560023-001-001, AS-560023-001-CH-001, AS-560023-001-FR-001                                                                                             |
| Packaging Specification        | 313025040-000                                                                                                                                             |
| Product Specification          | PS-560023-001-001                                                                                                                                         |
| Sales Drawing                  | SD-560023-002-000                                                                                                                                         |
| Test Summary                   | TS-560023-001-001                                                                                                                                         |



Series image - Reference only

|                                                                |               |
|----------------------------------------------------------------|---------------|
| EU ELV<br>Compliant                                            |               |
| EU RoHS<br>Compliant                                           | China RoHS    |
| REACH SVHC<br>Not Contained Per - D(2021)4569-DC (8 July 2021) |               |
| Halogen-Free<br>Status<br>Not Relevant                         |               |
| For more information, please visit <a href="#">Contact US</a>  |               |
| China ROHS                                                     | Not Relevant  |
| ELV                                                            | Compliant     |
| RoHS Phthalates                                                | Not Contained |

Search Parts in this Series

560023 Series

Use With

Mini50 Unsealed Single Row Receptacle [34791](#) , Mini50 Unsealed Dual Row Receptacle [34824](#)

|                                                                                                                                                                                 |                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| Application Tooling   <a href="#">FAQ</a>                                                                                                                                       |                           |
| Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document. |                           |
| Global                                                                                                                                                                          |                           |
| Description                                                                                                                                                                     | Product #                 |
| Hand Crimp Tool for CTX50 Unsealed Receptacle Terminals                                                                                                                         | <a href="#">638282000</a> |

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

560023-0445