

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0643241119

Status:


Active

Overview:

CMC and CMX Sealed, Hybrid, Modular Connectors

Description:

2.80mm, CMC CP Female Terminal, Tin plated; Selective 1.27µm Gold in Contact Area, for Tab Dimensions 2.80mm by 0.80mm, Wire Size > 3.00-5.00mm²



Documents:	
3D Model	Application Specification AS-64324-001-CH-001 (PDF)
3D Model (PDF)	Application Specification AS-64324-001-FR-001 (PDF)
Drawing (PDF)	Application Specification AS-98420-001-001 (PDF)
Product Specification PS-64326-001-001 (PDF)	Application Specification AS-98420-001-CH-001 (PDF)
Application Specification AS-64318-002-001 (PDF)	Application Specification AS-98420-001-FR-001 (PDF)
Application Specification AS-64318-002-CH-001 (PDF)	Application Specification AS-98420-001-SP-001 (PDF)
Application Specification AS-64318-002-FR-001 (PDF)	Packaging Specification PK-98910-001-001 (PDF)
Application Specification AS-64318-002-SP-001 (PDF)	RoHS Certificate of Compliance (PDF)
Application Specification AS-64324-001-001 (PDF)	

General	
Product Family	Crimp Terminals
Series	64324
Application	Automotive, Power, Wire-to-Wire
Comments	* Current tested on a fully loaded connector, current for temperature increase of 40°C. Current max = 21A for 2.80mm Terminal (5.00mm² wire)
Crimp Quality Equipment	Yes
Overview	CMC and CMX Sealed, Hybrid, Modular Connectors
Product Name	CMC, CP Terminal
UPC	883906128432
Physical	
Gender	Female
Material - Metal	High Copper Alloy
Material - Plating Mating	Tin
Material - Plating Termination	Gold
Net Weight	0.570/g
Packaging Type	Reel
Plating min - Mating	1.270µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	3.40-4.00mm
Wire Size AWG	10, 12
Wire Size mm²	>3.00-5.00
Electrical	
Current - Maximum per Contact	21.0A
Voltage - Maximum	14V DC
Solder Process Data	
Lead-freeProcess Capability	N/A
Material Info	

EU ELV Compliant	China RoHS
EU RoHS Compliant	
REACH SVHC	
Not Contained Per - D(2021)4569-DC (8 July 2021)	
Halogen-Free Status	
Low-Halogen	
For more information, please visit Contact US	
China ROHS	Green Image
ELV	Compliant
RoHS Phthalates	Not Contained

Search Parts in this Series
[64324 Series](#)

Use With
CMC Connector [64318](#) , [64321](#) , [64326](#) , [643251196](#)

Application Tooling | [FAQ](#)
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global	
Description	Product #
Hand Crimp	638119900
Tool for CP 2.8	
Receptacle 12-10	
AWG Type TXL Wire	
and>3.00-5.00mm²	
Type ID & ID Wire	
with 2.80mm²,	
CMC Wire Seal	
Receptacle	
Extraction Tool for	638132500
2.80mm CP Crimp	

Reference - Drawing Numbers
Application Specification

Crimp Specification
Packaging Specification
Product Specification
Sales Drawing

AS-64318-002-001, AS-64318-002-CH-001,
AS-64318-002-FR-001, AS-64318-002-SP-001,
AS-64324-001-001, AS-64324-001-CH-001,
AS-64324-001-FR-001, AS-98420-001-001,
AS-98420-001-CH-001, AS-98420-001-FR-001,
AS-98420-001-SP-001
CS-64324-001-001
PK-98910-001-001
PS-64326-001-001
SD-64324-001-001

Terminals for CMC
connector
Hand Crimp Tool for [638234100](#)
CP 2.8 Receptacle
Crimp Terminals
Mini-Mac Applicator [638950900](#)
for CP2.8 Crimp
Terminals 3.00 -
5.0mm² type ID & IR
Wire

This document was generated on 09/13/2021
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[64324-1119](#)