


98627-1001

2.50mm (.098") Pitch HDX Female Crimp Module, 15 Circuits, Circuit 1 to 15, Black



<u>Status</u>	Active
<u>Circuits / Positions</u>	15
<u>Pitch / Center Spacing</u>	2.50mm (.098")
<u>Rows</u>	1
<u>Product Name</u>	HDX
<u>Gender</u>	Female
<u>Stackable</u>	No
<u>Wire Entry Angle</u>	Right Angle
<u>Panel Mount</u>	No
<u>Current-max [amps]</u>	5.0A

RELATED PRODUCTS

<u>Mates With</u>	98623 , 98624 , 98625 , 98629 , 98630 , 98631
<u>Polarized to Mating Part</u>	Yes
<u>Lock to Mating Part</u>	Positive Lever
<u>Use With</u>	98587-0014

MECHANICAL

Contact Insertion Force-max. (per circuit)	10.00N (2.25 lb)
<u>Mating Force-max. (per circuit)</u>	15.00N (3.37 lb)
<u>Unmating Force-min. (per circuit)</u>	150.00N (33.72 lb)
Contact Retention Force-min. (per circuit)	60.00N (13.49 lb)

PHYSICAL

<u>Housing Material</u>	PBT Polyester, Glass-filled
<u>Flammability</u>	UL 94-HB
<u>Color</u>	Black
<u>Temperature Range</u>	-40°C to +85°C
<u>Designed In</u>	Millimeters
<u>Unmated Height</u>	51.90mm (2.043")
<u>Unmated Width</u>	23.40mm (.921")

REFERENCE

<u>Packaging</u>	Tray
<u>Comment</u>	Product needed for all HDX connectors to insert terminals
<u>Molex Series</u>	98627
<u>Marketing Series</u>	98627

ENVIRONMENT

RoHS Status ELV and RoHS Compliant

Features and Benefits

- Modular system
- Various connection possibilities within HDX series

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[98627-1001](#)